



XYT STACKED SYSTEM

ASME-NNNN-03-0365-0355xx

CHARON2 HD XYT (DXR+) with AccurET Modular

Data sheet

Version 1.0

PRELIMINARY

ETEL

AXIS DESIGNATION			
Number of controlled axes	3		
Axes name	X (bottom axis)	Y (top axis)	Theta
Thrust transmitter: DD (direct drive) or ID (indirect drive)	DD	DD	DD

TESTING CONDITIONS	UNIT			
Position controller	-	Modular 300 (7/15A)		Modular 300 (4/7.5A)
Motion controller	-	UltimET		
Rated payload	kg	-	-	2
Rated inertia	kg.m ²	-	-	0.018
Rated input voltage	VDC	300		96
Tool point position	mm	246.5 above bottom surface		
Ambient temperature	°C	22 ± 1		
Isolation system	-	QuiET		

DIMENSIONAL DATA	UNIT			
Width	mm	730		
Length	mm	839		
Height	mm	226.5		
Total stroke	mm or °	365	355	Infinite
Moving mass (without payload)	kg	30.6	11.4	-
Total mass (without payload)	kg	55		
Rotor inertia (without payload)	kg.m ²	-	-	0.004

FORCE / TORQUE CAPABILITIES (1)	UNIT			
Peak force / torque	N or Nm	953	658	7.87
Continuous force / torque	N or Nm	350	185	1.74
Standstill force / torque	N or Nm	264	140	1.32
Max. detent force / torque (average to peak)	N or Nm	26	16	0
Static friction (maximal value)	N or Nm	25	25	1
Dynamic friction (maximal value)	N/(m/s) or Nm/(rad/s)	25	25	0.03

LOAD CAPACITIES	UNIT			
Maximum payload	kg	30		

DYNAMIC PERFORMANCE	UNIT			
Duty cycle	%	25	60	10
Maximum speed	m/s or rad/s	2	2	30
Maximum acceleration	m/s ² or rad/s ²	20	20	180
Typical position stability at 2 kHz	nm or arcsec	±40	±40	±0.08

ACCURACY	UNIT			
Positioning accuracy (without mapping)	µm or arcsec	±20		±30
Positioning accuracy (with mapping)	µm or arcsec	±1		±3
Unidirectional repeatability	arcsec	-	-	±1
Bidirectional repeatability	µm or arcsec	±0.4		±2
Horizontal straightness / radial runout	µm	±3	±3.5	±3.5
Vertical straightness / total axial error	µm	±2.5	±5	±3
Orthogonality	arcsec	±15		-
Roll	arcsec	±5	±10	-
Pitch	arcsec	±5	±25	-
Yaw	arcsec	±10	±10	-

WORKING ENVIRONMENT	UNIT			
Clean room compatibility (2)	-	ISO 2		

ELECTRICAL SPECIFICATIONS (1)		UNIT	X (bottom axis)	Y (top axis)	Theta
	Motor type	-	Ironcore	Ironcore	Toothless
	Motor model	-	LMS15-050-3QC	LMG10-050-3QB	TTB0126-030-3NA-239
	Number of phases	-	3	3	3
Kt	Force constant	N/Arms or Nm/Arms	85.3	51.2	1.23
Ku	Back EMF constant (3)	Vrms/(m/s) or Vrms/(rad/s)	50.9	31	0.712
Km	Motor constant	Nm/√W	44.3	27.3	-
R20	Electrical resistance at 20°C (3)	Ohm	2.47	2.35	10.5
L1	Electrical inductance (3)	mH	23.8	13.7	2.65
Ip	Peak current	Arms	15	15	6.9
Ic	Continuous current	Arms	4.2	3.71	1.47
Is	Standstill current	Arms	3.18	2.81	1.11
ns	Standstill speed	m/s or rad/s	0.15	0.16	0.0016
Um	Max. input voltage	VDC	300	300	100
Pc	Max. cont. power dissipation	W	73.5	55.9	41.9
2τp	Magnetic period	mm	32	32	-
2p	Number of poles	-	-	-	28

ENCODER CHARACTERISTICS		UNIT			
	Encoder and signal type	-	Optical - incremental	Optical - incremental	Optical - incremental
	Output signal	-	1 Vpp	1 Vpp	1 Vpp
	Signal period or line count	μm or period/turn	4	4	18'000
	Reference mark	-	One	One	One
	Power supply	V	5	5	5

VACUUM CHARACTERISTICS		UNIT			
	Vacuum supply for wafer chuck				
	Vacuum at interface output	bar	-0.6		
	Vacuum supply for axis cleanliness				
	Vacuum flow	l/min	10	6	5

TYPICAL MOVE AND SETTLE TIMES		UNIT			
	Move 1: 10 μm within ±100 nm window	ms	40		-
	Move 2: 25 mm within ±100 nm window	ms	130		-
	Move 3: 80 mm within ±100 nm window	ms	180		-
	Move 4: 1 deg within ±40 μdeg	ms	-	-	100
	Move 5: 180 deg within ±40 μdeg	ms	-	-	500

GUIDING ELEMENTS					
	Type	-	Ball bearing	Ball bearing	Crossed roller bearing

MATERIAL AND FINISH					
	Baseplate	-	Anodized aluminum	Aluminium & silicon alloy	Aluminum alloy
	Carriage	-	Aluminium & silicon alloy	Anodized aluminum	Stainless steel

OPTIONS / ACCESSORIES / FEATURES					
	Temperature sensors	-	Yes	No	No

According to the Machinery Directive 2006/42/EC, the system presently described falls into the "partly completed machinery" category and fully complies with it as long as the system is operated according to the working conditions described in the corresponding manual. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the system is used in an improper way.

Notes: The specifications given may be mutually exclusive. Unless stated otherwise, all measurements are made within the testing conditions.

- (1) Tolerances on electrical parameters are available on request.
- (2) Under vertical laminar flow conditions at 0.5 m/s . Measured at tool point level. Contact ETEL for more details.
- (3) Terminal to terminal.