

MOTOR PERFORMANCE		Winding codes	TA	WA		
		UNIT	WATER COOLING	WATER COOLING		
Tp	Peak torque	Nm	308	284		
Ti	Intermittent torque	Nm	217	209		
Tc	Continuous torque	Nm	148	141		
Ts	Standstill torque	Nm	113	107		
Ip	Peak current	Arms	24.6	45.5		
Ii	Intermittent current	Arms	15.6	31.2		
Ic	Continuous current	Arms	9.88	19.7		
Is	Standstill current	Arms	7.49	14.9		
ns	Rated low speed	rpm	0.93	0.94		
nm	Maximum speed without flux weakening	rpm	429	903		
nm,FW	Maximum speed with flux weakening	rpm	1570	2880		
ton,p	Maximum ON time for peak cycle	s	4.7	5.9		
ton,i	Maximum ON time for intermittent cycle	s	2.7	2.7		
Pp	Power dissipation @ Ip	W	12500	10300		
Pi	Power dissipation @ Ii	W	6220	6050		
Pc	Power dissipation @ Ic	W	2490	2420		
Td	Max. detent torque (average to peak)	Nm	2.1	2.1		

MOTOR SETTING		UNIT				
Kt	Torque constant	Nm/Arms	15.9	7.59		
Ku	Back EMF constant (*)	Vrms/(rad/s)	9.25	4.40		
Km	Motor constant	Nm/√W	3.69	3.54		
R20	Electrical resistance at 20°C (*)	Ohm	12.5	3.07		
Ld/Lq	Electrical inductance (*)	mH	100 / 96.9	22.7 / 22.0		
Isc	Maximum short-circuit current	Arms	13.3	28.0		
nb	Base speed	rpm	253	667		
nb,i	Base speed at intermittent duty cycle	rpm	169	530		
nb,p	Base speed at peak duty cycle	rpm	112	447		
nn	Rated speed	rpm	216	588		
Tn	Rated torque	Nm	147	138		
In	Rated current	Arms	9.86	19.5		
rth	Thermal time constant	s	80.3	80.1		
Rth	Thermal resistance	K/W	0.0361	0.0363		
2p	Number of poles	-	16	16		
J	Rotor inertia	kg·m²	0.00662	0.00662		
mr	Rotor mass	kg	4.39	4.39		
ms	Stator mass	kg	14.3	14.2		

MOTOR ENVIRONMENT		UNIT				
Udc	Nominal DC bus voltage	VDC	600	600		
Di	Intermittent duty cycle	%	40	40		
Dp	Peak duty cycle	%	5.0	5.0		
Sr	Rotor exchange surface	m²	0.074	0.074		
θamb	Ambient temperature	°C	20	20		
θmax	Maximum coil temperature	°C	130	130		
θw	Inlet water temperature	°C	20	20		
Δθw	Water temperature difference for Pc	K	5.0	5.0		
qw	Minimum water flow for Δθw	l/min	7.8	7.6		
Δpw	Max. pressure drop at qw	bar	0.4	0.4		


Notes: (*) terminal to terminal.

Hypotheses and tolerances are in ETEL Integration Manual.


Please refer to ETEL Integration Manual for the mass of the optional cooling jacket and the possible additional pressure drop.

Caution: Any use of the motor beyond speed/torque limit could lead to hazardous voltage and serious injuries. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the motor is used in an improper way.


TA - WATER COOLING



TA - WATER COOLING



WA - WATER COOLING



WA - WATER COOLING

